
The drawing, specifications, and concepts contained here is an the sole property of Dark Aerospace Eugene, OR.

REV ECR DESCRIPTION

DATE INITIAL APPROVED DISTANDARDS. 1 DELETED DIM. 122. ADDED DIM. 138. -3 DELETED DIM.



<u>NOTE:</u> REF. BELL T/N: 412-210-001-101.

DART

M/R HUB ASSEMBLY PIN

RBT400268

MAT'L

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
.XX ± .005 FRACTIONS ± 1/8
.XX ± .01 ANGLES ±.5°
.X ± .1

1. BREAK ALL SHARP EDGES .015 x 45°
OR .015R

DRAWN BY: PERRITT
APPROVED
HEAT
FREAT
FINISH
SPEC
USED ON MODEL


1. BREAK ALL SHARP EDGES .015 x 45* OR .015R OR

DWG NO.

BELL 412							
5/2009	SHEET 1 OF 3						


REV


ASSY QTY	ASSY QTY	В/О	Part #	UNIT	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.	
			-1	1	SHAFT	4140 Q&T/ 4142 Q&T		2	1
			-3	1	CLAMP	304 S.S.		3	Ľ
		B/O	-5	1	NUT	STEEL	AN315-8	1	




This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	REVISIONS										
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED						
1	15-0125	-3 DELETED OPTIONAL CORNER RELIEF.	6/2/2015	DPD	JAG						







-3)

CLAMP